
Diversco



CARBON DIOXIDE & BEVERAGE GAS PRODUCTS











TF: 800.650.0061
E: igas@diversco.com

495 Conestoga Blvd.
Cambridge, On
N1R 7P4

CARBON DIOXIDE CYLINDER SPECIFICATIONS

PART #	WATER CAPACITY			DIAMETER		LENGTH		CYLINDER WEIGHT		CO_2		NITROGEN
	cu in	lbs	liters	in	mm	in	mm	lbs	kgs	lbs	kgs	cu ft
B50	2035	73.5	33.3	8.60	218.4	46.3	1175	48.3	21.9	50.0	22.7	144.0
B35	1426	51.5	23.4	8.00	203.2	37.8	960	35.2	16.0	35.0	15.9	100.9
B22	901	32.5	14.7	8.00	203.2	25.1	638	25.3	11.5	22.0	10.0	63.5
B20	814	29.4	13.3	8.00	203.2	23.2	589	23.7	10.8	20.0	9.1	57.6
B15	612	22.1	10.0	6.89	175.0	23.1	587	16.8	7.6	15.0	6.8	43.3
B10	407	14.7	6.70	6.89	175.0	16.5	419	12.6	5.7	10.0	4.5	29.0
B5	203	7.4	3.40	5.25	133.4	14.2	361	6.3	2.9	5.0	2.3	14.5
B2.5	102	3.7	1.70	4.38	111.3	10.3	262	3.3	1.5	2.5	1.1	7.2
B2	83.0	3.0	1.40	4.38	111.3	8.5	213	2.9	1.3	2.0	0.9	5.9
B1.75	71.4	2.6	1.17	3.21	81.4	12.5	317	1.9	0.9	1.75	0.8	5.1
B1.5	61.2	2.2	1.00	3.21	81.4	11.1	281	1.7	0.8	1.5	0.7	4.3
B1	40.7	1.5	0.66	3.21	81.5	7.8	197	1.4	0.6	1.0	0.5	2.9

Service Pressure: - 1800 psi / 124 bar

Specification: - DOT-3AL & TC-3ALM designed
- ISO design cylinders are available

Alloy: - Manufactured from high strength aluminum alloy 6061-T6

Threads: - B5 and larger supplied with 1.125-12 UNF thread, all others with .750-16 UNF thread
- Other thread sizes available upon request

Markings: - As required by specification, inclusive of tare weight
- Additional markings available upon request

Finish: - Standard finish is brushed body with unpainted crown

Graphics: - Logos or labels in silkscreen or Duragrafix available upon request

Common Configuration: - B10 and larger available with valve and carrying handle, B5 and smaller with valve only
- Caps & collars or dip tubes available upon request

VALVES

BRASS VALVES



SHERWOOD

PART NUMBER	THREAD DESCRIPTION
GSV 32051-28LX75	0.75-16UNF
GSV 32051-28LX	1.125-12UNF



cavagna group

PART NUMBER	THREAD DESCRIPTION
CBA 3 320 1 3000	0.75-16UNF
CBG 9 320 1 3000	1.125-12UNF

CHROME PLATED VALVES



SHERWOOD


PART NUMBER	THREAD DESCRIPTION
GSVA 32051-28-75	0.75-16UNF
GSVA 32051-28LX	1.125-12UNF



cavagna group

PART NUMBER	THREAD DESCRIPTION
CDA 3 320 1 3000	0.75-16UNF
CDG 9 320 1 3000	1.125-12UNF

BRASS CGA CYLINDER TO REGULATOR ADAPTORS




CGA 320-580 3000PSI

PART NUMBER	DESCRIPTION
A-809	Carbon Dioxide Cylinder (CGA-320) Argon, Helium, or Nitrogen Regulator (CGA-580)
A-810	1 pc. Adapter Carbon Dioxide Cylinder (CGA-320) Argon, Helium, or Nitrogen Regulator (CGA-580)

CARBON DIOXIDE GAS ACCESSORIES

REGULATOR INLET NUTS & NIPPLES











CGA 320 3000PSI

PART NUMBER	PART	MATERIAL	DESCRIPTION
N-61	Nut	Brass	.830”-14NGO-RH-INT
N-61SS	Nut	SS	.830”-14NGO-RH-INT
MN-061	Nut	CP Brass	.830”-14NGO-RH-INT
HTN-61	Nut-HT	Brass	.830”-14NGO-RH-INT
HTN-61P	Nut-HT	Brass, Plastic Grip	.830”-14NGO-RH-INT
MHN-061P	Nut-HT	CP Brass, Plastic Grip	.830”-14NGO-RH-INT
NP-147	Nipple*	Brass	1/4” NPT, 2” Long
NP-147SS	Nipple*	Brass	1/4” NPT, 2” Long
MNP-147	Nipple*	CP Brass	1/4” NPT, 2” Long
NP-150	Nipple*	Brass	1/4” NPT, 2.5” Long
NP-150SS	Nipple*	SS	1/4” NPT, 2.5” Long
MNP-150	Nipple*	CP Brass	1/4” NPT, 2.5” Long
NP-151	Nipple*	Brass	1/4” NPT, 3” Long
MNP-151	Nipple*	CP Brass	1/4” -NPT, 3” Long
NP-154SS	Nipple*	SS	1/4” NPT, 3.5” Long
NP-152	Nipple*	Brass	1/2” 27UNS, 2.5” Long
NP-150T3	Nipple-HT**	Brass	1/4” NPT, 2.5” Long
NP-147T3C2	Nipple-HT**	Brass	For 1/4” Tube
NP-147T3C3	Nipple-HT**	Brass	For 5/16” Tube

*Includes Washer **Replace Washer with W-10 only

VALVE OUTLET ADAPTERS





CGA 320 3000PSI

PART NUMBER	MATERIAL	MALE & FEMALE PIPE THREADS
A-541	Brass	.825” 12NGO-RH-EXT x 1/4 MNPT
A-542	Brass	.825” 12NGO-RH-EXT x 3/8 MNPT
A-543	Brass	.825” 12NGO-RH-EXT x 1/2 MNPT
A-543CV	Brass	.825” 12NGO-RH-EXT x 1/2 MNPT
N-854A	Brass	.825” 12NGO-RH-EXT x 1/4 FNPT